



1130 SERIES STANDARD PRESSURE GAUGE WITH ABS CASE MODEL:1130



Applications:

1130 series standard gauge is for use specially in measuring water level, such as in central heating system. Also available for any other applications that do not attack the brass measuring system.

Specifications:

Nominal sizes:

1.5", 2", 2.5"

Connection:

BSP 1/8" for 1.5" BSP 1/4" for 2", 2.5"

Scale Range, according to EN 837-1/5

Pressure ranges: 0 to 0.6/1/1.6/2.5/4/6/10/16/25 bar

Operating Temperature:

Ambient: -20°C to 60°C, medium: 60°C maximum

Material Specification:

Case: ABS Window: snap on clear acrylic

Wetted parts: copper alloy bourdon tube and brass connection,

Movement: brass







Options:

NPT, BSPT or other process connection Double dial range or other dial ranges Snap in acrylic window

DIMENSION:





DIAL SIZE	Model	A	В	C	D
1.5"	Lower mount	Ø 41	23.5	20.5	11
	Back mount	Ø 51	24	20.5	11
2"	Lower mount	Ø 50	27	25	14
	Back mount	Ø 50	27	25	14
2.5"	Lower mount	Ø 62	29	31	14
	Back mount	Ø 62	29	31	14

dimensions are approximate and can be changed wthout prior notice

www.hidropaks.com.tr