CAPSULE AND DIAPHRAGM PRESSURE GAUGE





1400 SERIES CAPSULE LOW PRESSURE GAUGE MODEL:1400



Application:

1400 series capsule low pressure gauge is suitable for dry and gaseous media that does not attack copper alloy parts. It is mainly used for medical, vacuum, laboratory technology for contents measurement and filter monitoring.

Specifications:

Nominal sizes:

2.5", 3.5", 4,5"

Connection:

BSP 1/4" for 2.5", 3.5", 4.5"

Scale Range, according to EN 837-1/5

Pressure ranges: 0 to 16/25/40/60/100/160/250/400/600/1000mbar Vacuum range: -600/-400/-250/-160/-100/-60/-40/-25/-16/ to 0 mbar

Operating Temperature:

Ambient: -20°C..+60°C

Medium: +60°C maximum

Material Specification:

Case & window: 2.5", 3.5" with black steel case and screw on acrylic window

4.5" with black steel case and bezel, instrument glass window

Wetted parts: copper capsule, brass connection

Movement: brass

32 www.hidropaks.com.tr








Options:

NPT, BSPT or other process connection Restrictor Double dial range or other dial ranges 304 Stainless steel case

DIMENSION:







DIAL SIZE	A	В	B1	С	D	Н	Е
2.5"	Ø 66.8	38	32	21	55.6	67.5	9.6
3.5"	Ø 93.7	40	43	21	69	93	9.6
4.5"	Ø 121.5	37.3	18-16	1885	85.8		20.5

dimensions are approximate and can be changed wthout prior notice

www.hidropaks.com.tr 33